


# VC-RAD 31-90° ELECTRIC TORQUE MULTIPLIER – TECHNICAL DATA



# VC-RAD 31-90° ELECTRIC TORQUE MULTIPLIER – TECHNICAL DATA

## **DESCRIPTION**

The VC-RAD 31-90° Electric Torque Multiplier is a hand held, non-impacting electrically driven power tool designed to apply torque to tighten and remove threaded fasteners.

The tool incorporates a  $90^{\circ}$  gearbox to reduce its overhead height and incorporates an extra rotatable lifting handle.

The reaction force works in the opposite direction to the applied torque. The point of reaction should be kept as far away as practicable from the centre of the gearbox to minimise this force.

Torque is controlled by adjusting the torque setting dials. Corresponding settings and torques are determined using the calibration certificate provided.

The VC-RAD 31-90° must always be operated with the following:-

- 110v or 240v Electrical Supply (Dependant on model purchased)
- Impact Quality Sockets
- Reaction Arm

### **SPECIFICATION**

Output Square Drive (Male): Direction: Torque Accuracy: Minimum Output Torque: Maximum Output Torque: Speed: Power Supply Voltage: Electric Motor Input Power: Electric Motor Output Power: Noise: Vibration: Tool Weight:	1" (25.4mm) Forward & Reverse +/- 10% 1,100 Nm (811 lbf.ft) 3,100 Nm (2,286 lbf.ft) 4 rpm (Single) 110V or 240V (dependant on model purchased) 850 Watts 480 Watts Less than 80 dB(A) Vibration level at handle does not exceed 2.5m/sec 7.1 Kg (15.65 lbs)
Tool Weight:	7.1 Kg (15.65 lbs)
Reaction Plate Weight:	2.04 Kg (4.5 lbs)

### **ACCESSORIES AVAILABLE**

The following accessories are available upon request and can be custom made to suit requirements. Please contact W. Christie (Industrial) Limited for more information:-

- Special Reactions
- Nose Cone Extensions
- Offset Gearbox
- Impact Quality Sockets
- Torque Checking System (Rundown Fixture)

No statement or data within this literature is warranted or guaranteed to be accurate.

